GP Lighting

Product Data Sheet

GP LD GBS125 E27 5-25W EW SPFM

Order code	EAN	Packaging - SKU	
085195-LDB1	4986149085195	Colour gift box, 1 pc/SKU	
		5 , 1	
B			
Product		l. == .	
Category		LED Lamps	
Series		VINTAGE EXTRA WARM LIGHT	
		(SPIRAL FILAMENT)	
Model		GLOBE FILAMENT EXTRA WARM SPIRAL	THI I
		EXTRA WARIN SFIRAL	
Description		GP LD GBS125 E27 5-25W 220-240V EW SPFM	
General description	on.		
	UII	A	
Energy label			
Lamp shape		Globe	
Lamp base		E27	
Dimmable		No	
Mercury free		Yes	1 1
Mercury content		0.0 mg	
Recycling		Yes	
Electrical characteristics			
Nominal wattage		5 W 10	
Rated wattage		5 W	
Equivalent incandescent lamp power		25 W	
Power factor		0.5	Spectral Distribution
Voltage		220-240 V	
Operating frequency		50/60Hz	Spectrum 1.0=7.726mW/nm
Lamp current		32.4-48.4 mA	1,0-
Weighted Energy Consumption		5 KWh / 1000 h	0.0-
Weighted Energy Col	nsumption	3 KWII7 1000 II	-
light tooknigel oh	aractoristics		0.6-
Light technical characteristics			0.4-
Light colour		EXTRA WARM WHITE	- 0.2-
Colour temperature		2000 K /K	
Colour rendering index (Ra)		≥80	0.0 513 675 838 1000 Wavelength(nm)
Colour consistency		<6 SDCM	
Nominal luminous flu	X	250 lm ±10%	
Rated luminous flux		250 lm	GP LED Lamps are designed for
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard
Warm-up time (60%)		<1s	incandescent lamps.
Starting time		Instant	 Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		20000	Instant start with full light output
Executive Execut			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		170 mm + 2 mm	_
- ::		178 mm ±2 mm	• No UV
Diameter (D)		125 mm ±2 mm	1
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
			 Can be used everywhere at home
			Use outdoors only in enclosed and
			ventilated luminaires

www.gp-lighting.com